

# Product Environmental Profile



## DELPHYS XM

High power density and superior efficiency UPS  
300 to 800 kVA/kW



### The commitments of Socomec to respect the environment

As part of its environmental policy, Socomec is committed to:

- Incorporate the principles of the circular economy into the design of new products and services
- Promote longer product lifetimes
- Promote the use of environmentally responsible materials
- Design and develop solutions to further improve the energy efficiency of our products and services
- Inform our customers in a transparent manner about the environmental impact of our products throughout their life cycle.

To this end, Socomec is committed to constantly monitoring, anticipating and complying with environmental regulations as well as customer expectations relating to its products, and to ensuring that all those involved adhere to and take responsibility for its commitments.

Socomec is member of :



Member of WEEE Europe



Environment and sustainable development commissions



PEP ecopassport® Registration number: SOCO-00137-V01.01-EN

SOCOMECS.A.S

Head office : 1, rue de Westhouse – F – B.P.60010 – 67235 Benfeld Cedex

Tél : 03 88 57 41 41 – Fax : 03 88 57 78 78 – [www.socomec.com](http://www.socomec.com)

Contact : [http://www.socomec.com/contact-us\\_en.html](http://www.socomec.com/contact-us_en.html)



## ● Product information :

| Reference product              |                                            |
|--------------------------------|--------------------------------------------|
| Model                          | DXM 600KVA PARALLEL                        |
| Sales reference                | 3DMA600P6-00000                            |
| Description                    | Uninterruptible power supply up to 800 kVA |
| General data                   |                                            |
| UPS Configuration              | Single                                     |
| UPS topology                   | Double conversion                          |
| UPS Performance classification | VFI-SS-11                                  |
| Number of phases available     | Three phase                                |
| Power [W]                      | 600000                                     |
| Apparent power [VA]            | 600000                                     |
| Acoustic noise [dB]            | 72,3                                       |
| Efficiency                     |                                            |
| Weighted UPS efficiency [%]    | 96,93%                                     |
| Weight & dimensions            |                                            |
| Dimensions W*H*D [mm]          | 1120*915*2150                              |
| Mass without packaging [kg]    | 757,04                                     |
| Mass of the packaging [kg]     | 39,96                                      |

The UPS is not equipped with an energy storage system.

### Functional unit :

To ensure the supply of power to remain within specified characteristics to equipment with load of 100 watts for a RSL of 1 years.

### Declared unit :

To ensure the supply of power to remain within specified characteristics to equipment with load of 600000 watts for a RSL of 15 years.

*Mathematic relation between DU (declared unit) and FU (functional unit) mentioned in PSR-0010-ed2.0-EN 2023 12 08*

### References covered by this PEP with extrapolation rules:

- DXM 600KVA PARALLEL with sales reference: 3DMA600P6-00000
- DXM 600KVA SINGLE UNIT with sales reference: 3DMA600S6-00000
- DXM 300KVA PARALLEL UNIT with sales reference: 3DMA300P3-00000
- DXM 300KVA SINGLE UNIT with sales reference: 3DMA300S3-00000
- DXM 400KVA PARALLEL with sales reference: 3DMA400P4-00000
- DXM 400KVA SINGLE UNIT with sales reference: 3DMA400S4-00000
- DXM 500KVA PARALLEL with sales reference: 3DMA500P5-00000
- DXM 500KVA SINGLE UNIT with sales reference: 3DMA500S5-00000
- DXM 600KVA PARALLEL with sales reference: 3DMA600P6-00000
- DXM 600KVA SINGLE UNIT with sales reference: 3DMA600S6-00000
- DXM 800KVA SINGLE CABINET with sales reference: 3DMA800S8-00000
- DXM 800KVA PARALLEL SWITCH VER with sales reference: 3DMD800P8-00000
- DXM 800KVA SINGLE SWITCH VER with sales reference: 3DMD800S8-00000

## Characteristics of the covered references:

| Model                              | Power [W] | Weighted UPS efficiency [%] | Product mass [kg] | Packaging mass [kg] |
|------------------------------------|-----------|-----------------------------|-------------------|---------------------|
| Declared Unit: 3DMA600P6-00000     | 600000    | 96,93%                      | 757               | 40                  |
| Extrapolated unit: 3DMA600S6-00000 | 600000    | 96,93%                      | 757               | 40                  |
| Extrapolated unit: 3DMA300P3-00000 | 300000    | 96,95%                      | 525               | 40                  |
| Extrapolated unit: 3DMA300S3-00000 | 300000    | 96,95%                      | 525               | 40                  |
| Extrapolated unit: 3DMA400P4-00000 | 400000    | 96,98%                      | 568               | 40                  |
| Extrapolated unit: 3DMA400S4-00000 | 400000    | 96,98%                      | 568               | 40                  |
| Extrapolated unit: 3DMA500P5-00000 | 500000    | 96,93%                      | 660               | 40                  |
| Extrapolated unit: 3DMA500S5-00000 | 500000    | 96,93%                      | 660               | 40                  |
| Extrapolated unit: 3DMA600P6-00000 | 600000    | 96,93%                      | 899               | 50                  |
| Extrapolated unit: 3DMA600S6-00000 | 600000    | 96,93%                      | 899               | 50                  |
| Extrapolated unit: 3DMA800S8-00000 | 800000    | 96,98%                      | 864               | 40                  |
| Extrapolated unit: 3DMD800P8-00000 | 800000    | 96,98%                      | 1251              | 40                  |
| Extrapolated unit: 3DMD800S8-00000 | 800000    | 96,98%                      | 1251              | 40                  |

## ● Materials and substances

### Declaration of the constitutives materials

Total mass of the DXM 600KVA PARALLEL (including packaging): 797 kg among which packaging: 39,96 kg

For the reference product:

| Plastics as % of weight  |       | Metals as % of weight    |        | Other as % of weight    |        |
|--------------------------|-------|--------------------------|--------|-------------------------|--------|
| Polyester                | 1,03% | Stainless steel          | 47,75% | Electronic components   | 17,28% |
| Polyamide                | 0,44% | Copper and its alloys    | 19,18% | Other inorganics        | 0,70%  |
| Epoxy resin              | 0,42% | Other ferrous alloys     | 6,52%  | Wood                    | 0,13%  |
| PE                       | 0,25% | Aluminium and its alloys | 4,76%  | Cardboard               | 0,13%  |
| ABS                      | 0,19% | Steel                    | <0,1%  | Other organics          | <0,1%  |
| PC                       | 0,15% | Zinc and its alloys      | <0,1%  | Paper                   | <0,1%  |
| PET                      | 0,13% | Tin and its alloys       | <0,1%  |                         |        |
| PBT                      | <0,1% | Lead and its alloys      | <0,1%  |                         |        |
|                          |       |                          |        |                         |        |
|                          |       |                          |        |                         |        |
|                          |       |                          |        |                         |        |
| Other plastics           | 0,71% |                          |        |                         |        |
|                          |       |                          |        |                         |        |
| Total Plastics: 26,48 kg |       | Total Metals: 624,58 kg  |        | Total Others: 145,94 kg |        |
|                          | 3,32% |                          | 78,37% |                         | 18,31% |

### Substances management

Socomec is leading a program to limit the use of hazardous substances in the design of new products and to monitor the presence of substances of concern in its supplies to anticipate future use restrictions.



Directive 2011/65/EU : Product references covered by this PEP meet the requirements of the RoHS Directive on the restriction of substances such as lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyl (PBB), polybrominated diphenyl ethers (PBDEs) and phthalates (DIBP, DEHP, BBP, DBP).



REACH 1907/2006 regulation: To the best of our knowledge, based on the supplier declarations, at the publication date of this document, the product do not contain any SVHC in a concentration above 0,1% per weight.

## ● Manufacturing

The products covered by this PEP are manufactured on a production site in China a site where impacts on the environment are reduced by optimizing its energy consumption and by practicing a rigorous waste management. Moreover, Socomec is committed to the progressive ISO 14001 certification of its manufacturing sites.

## ● Distribution

As part of its distribution policy aiming to respect the environment, Socomec is in favor of groupage transports and ISO 14001 certified logistic partners.

No reconditionning is planned for the product. This phase is consequently neglected.

The sizing of the packaging has been optimized to ensure the best possible protection of the product at the lowest possible volume in order to reduce the impact of the transport stage on the environment.

## ● Installation

The installation phase consists in connecting the product to the existing electrical installation.

The installation does not generate any significant impacts on the environment, except impacts from packaging waste.

## ● Use phase

### Consumption scenario

Use phase scenario: European energy mix

| Load (%)                     | 25% | 50% | 75% | 100% |
|------------------------------|-----|-----|-----|------|
| Proportion of time spent (%) | 25% | 50% | 25% | 0%   |

Total energy consumption during 15 years

| Total average energy consumption | 1207238 kWh |
|----------------------------------|-------------|
| Average UPS efficiency           | 96,93%      |

### Care and maintenance

It is recommended to carry out periodic specialized maintenance in order to keep the equipment at the maximum level of efficiency and to avoid the installation being out of service with possible damage/risks.

Typical parts which are subjects to maintenance:

| Components            | DC capacitor filtering | AC capacitor filtering | Fans | Power supply PCB |
|-----------------------|------------------------|------------------------|------|------------------|
| Number of replacement | 2                      | 2                      | 3    | 2                |

### Consumables

The product does not require consumables.





● End of life

End of life treatment

The following parts require specific care and selective treatment in accordance with Annex VII of the WEEE Directive 2012/19/EU:

| Type of component          | Part mass | Location |
|----------------------------|-----------|----------|
| PCBA                       | 236,58 kg | 1        |
| LCD                        | 0,54 kg   | 2        |
| Capacitors                 | 2,86 kg   | 3        |
| Lithium metal coin battery | 0,006 kg  | 4        |



Waste of electrical and electronic equipment. Maintenance and disassembly should always be conducted by qualified personnel.

Recyclability potential of the product according to IEC TR 62635

The recyclability potential of the product is 81,52%.

This covers material and energy recovery potentials.

● Additional information



This environmental declaration lists the information required in Annex A and B of IEC 62040-4 (Edition 1.0 2013-04) and EN 62040-4:2013 (2014-03).

● Environmental impacts

Calculation methodology: life cycle assessment (LCA)



The calculation of the impacts on the environment was made using a life cycle assessment methodology in accordance with the ISO 14040 requirements and with PEP eco passport product category rules.

For more details follow the link:

[www.pep-ecopassport.org](http://www.pep-ecopassport.org)

This study was carried out with the following version of the software EIME and of the database:

EIME version: EIME v6.2.5-9

Database version: CODDE-2024-04 - Updated on 2024-06-04

For biogenic carbon storage the following methodology was used : 0/0

# PRODUCT ENVIRONMENTAL PROFILE

The whole life cycle has been taken into account:

| Step                             | Geographical representativeness                                                                                      | Scenario                                                                                                                                                          |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Manufacturing (M) (A1-A3)</b> | Production of electronic components : Asia<br>Production of other components and packaging : Asia<br>Assembly : Asia | From the raw material extraction to the last Socomec logistic platform, including packaging<br>Waste generated during manufacturing phase are taken into account. |
| <b>Distribution (D) (A4)</b>     | Distribution scenario : Europe                                                                                       | From the last Socomec logistic platform to the final customer.<br>No product reconditionning.                                                                     |
| <b>Installation (I) (A5)</b>     | Transport and treatment of packaging wastes : Local                                                                  | Local road transport of 1000 km of generated wastes to the treatment site, end of life treatment.                                                                 |
| <b>Use phase (U) (B1-B7)</b>     | Energy mix : Europe<br>Production of maintenance components: analog to manufacturing phase                           | Power consumption required during 15 years according to consumption scenario above mentionned.                                                                    |
| <b>End of life (EOL) (C1-C4)</b> | Transport and treatment : Local                                                                                      | Road transport of 1000 km from the final customer to the treatment sites.<br>End of life treatment.                                                               |

## Environmental impacts of the DXM 600KVA PARALLEL per functional unit (power of 100W and a lifespan of 1 year)

The following impacts have been calculated to best represent geographically, temporally and technologically each step of the life cycle.

| Indicators                                        | Unit               | Total impact | M (A1-A3) | D (A4)   | I (A5)   | U (B1-B7) | EOL (C1-C4) |
|---------------------------------------------------|--------------------|--------------|-----------|----------|----------|-----------|-------------|
| Climate change                                    | kg CO2 eq.         | 4,94E+00     | 1,68E-01  | 2,67E-03 | 0*       | 4,77E+00  | 7,20E-04    |
| Climate change-Biogenic                           | kg CO2 eq.         | 1,04E-02     | 1,36E-03  | 0*       | 1,68E-04 | 8,88E-03  | 0*          |
| Climate change-Fossil                             | kg CO2 eq.         | 4,93E+00     | 1,67E-01  | 2,67E-03 | 0*       | 4,76E+00  | 7,20E-04    |
| Climate change-Land use and land use change       | kg CO2 eq.         | 5,20E-08     | 5,18E-08  | 0*       | 0*       | 1,94E-10  | 0*          |
| Ozone depletion                                   | kg CFC-11 eq.      | 4,79E-08     | 1,92E-08  | 0*       | 0*       | 2,87E-08  | 8,24E-12    |
| Acidification                                     | mol H+ eq.         | 2,66E-02     | 1,76E-03  | 9,27E-05 | 0*       | 2,47E-02  | 3,83E-06    |
| Eutrophication, freshwater                        | kg P eq.           | 1,48E-05     | 2,17E-06  | 0*       | 0*       | 1,26E-05  | 9,32E-08    |
| Eutrophication, marine                            | kg N eq.           | 3,17E-03     | 1,57E-04  | 2,19E-05 | 0*       | 2,99E-03  | 1,67E-06    |
| Eutrophication, terrestrial                       | mol N eq.          | 4,98E-02     | 1,71E-03  | 2,39E-04 | 0*       | 4,78E-02  | 1,70E-05    |
| Photochemical ozone formation - human health      | kg NMVOC eq.       | 1,01E-02     | 5,91E-04  | 6,16E-05 | 0*       | 9,43E-03  | 4,42E-06    |
| Resource use, minerals and metals                 | kg SB eq.          | 4,85E-04     | 3,86E-04  | 0*       | 0*       | 9,93E-05  | 0*          |
| Resource use, fossils                             | MJ                 | 1,24E+02     | 3,89E+00  | 3,37E-02 | 0*       | 1,20E+02  | 0*          |
| Water use                                         | m3 eq.             | 9,92E-01     | 6,12E-01  | 0*       | 0*       | 3,80E-01  | 0*          |
| Particulate matter                                | Disease occurrence | 2,08E-07     | 9,34E-09  | 4,88E-10 | 0*       | 1,98E-07  | 2,83E-11    |
| Ionising radiation, human health                  | kBq U235 eq.       | 1,44E+01     | 6,85E+00  | 0*       | 0*       | 7,60E+00  | 0*          |
| Ecotoxicity, freshwater                           | CTUe               | 1,09E+01     | 1,79E+00  | 1,59E-03 | 0*       | 9,11E+00  | 4,41E-03    |
| Human toxicity, cancer                            | CTUh               | 2,10E-07     | 2,06E-07  | 0*       | 0*       | 4,43E-09  | 0*          |
| Human toxicity, non-cancer                        | CTUh               | 5,08E-08     | 3,55E-08  | 0*       | 0*       | 1,53E-08  | 0*          |
| Land use                                          | No dimension       | 1,35E-01     | 4,48E-03  | 0*       | 0*       | 1,31E-01  | 0*          |
| Renewable primary energy used as energy           | MJ                 | 3,17E+01     | 7,92E-02  | 0*       | 0*       | 3,16E+01  | 0*          |
| Renewable primary energy used as raw material     | MJ                 | 9,92E-04     | 9,92E-04  | 0*       | 0*       | 0*        | 0*          |
| Total renewable primary energy                    | MJ                 | 3,17E+01     | 8,02E-02  | 0*       | 0*       | 3,16E+01  | 0*          |
| Non renewable primary energy used as energy       | MJ                 | 1,24E+02     | 3,87E+00  | 3,37E-02 | 0*       | 1,20E+02  | 0*          |
| Non renewable primary energy used as raw material | MJ                 | 2,50E-02     | 1,86E-02  | 0*       | 0*       | 6,42E-03  | 0*          |
| Total non renewable primary energy                | MJ                 | 1,24E+02     | 3,89E+00  | 3,37E-02 | 0*       | 1,20E+02  | 0*          |
| Total primary energy                              | MJ                 | 1,56E+02     | 3,97E+00  | 3,38E-02 | 0*       | 1,52E+02  | 0*          |
| Use of secondary material                         | kg                 | 7,75E-07     | 7,07E-07  | 0*       | 0*       | 6,76E-08  | 0*          |
| Use of renewable secondary fuels                  | MJ                 | 0,00E+00     | 0*        | 0*       | 0*       | 0*        | 0*          |
| Use of non renewable secondary fuels              | MJ                 | 0,00E+00     | 0*        | 0*       | 0*       | 0*        | 0*          |
| Net use of fresh water                            | m3                 | 2,32E-02     | 1,42E-02  | 0*       | 0*       | 8,94E-03  | 0*          |
| Hazardous waste disposed                          | kg                 | 6,33E+00     | 6,08E+00  | 0*       | 0*       | 2,57E-01  | 0*          |
| Non hazardous waste disposed                      | kg                 | 8,60E-01     | 4,23E-02  | 0*       | 0*       | 8,09E-01  | 8,80E-03    |
| Radioactive waste disposed                        | kg                 | 2,12E-04     | 2,33E-05  | 5,65E-08 | 0*       | 1,88E-04  | 1,34E-07    |
| Components for reuse                              | kg                 | 0,00E+00     | 0*        | 0*       | 0*       | 0*        | 0*          |
| Materials for recycling                           | kg                 | 1,35E-04     | 1,20E-07  | 0*       | 1,35E-04 | 0*        | 0*          |
| Materials for energy recovery                     | kg                 | 0,00E+00     | 0*        | 0*       | 0*       | 0*        | 0*          |
| Exported Energy                                   | MJ                 | 1,32E-04     | 1,32E-04  | 0*       | 0*       | 0*        | 0*          |
| Biogenic carbon content - Product                 | kg of C            | 0,00E+00     | 0*        | 0*       | 0*       | 0*        | 0*          |
| Biogenic carbon content - Packaging               | kg of C            | 1,67E-05     | 1,67E-05  | 0*       | 0*       | 0*        | 0*          |

NB : 0\* means that this impact either represents less than 0.01% of the total life cycle of the reference flow, or has no impact (in the case where the total impact is zero).

# PRODUCT ENVIRONMENTAL PROFILE

The aforementioned impacts are declared for the functional unit of the reference product.

The environmental impacts of the reference product per declared unit can be calculated by multiplying the values of the environmental indicators by the factor available in the following table.

| Life cycle phase | All life cycle phase |
|------------------|----------------------|
| Factor           | 90000                |

|                                                                                                                                                                                                                                                        |                                                                                                            |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|
| Registration number : SOCO-00137-V01.01-EN                                                                                                                                                                                                             | Drafting Rules : "PEP-PCR-ed4-EN 2021 09 06"<br>Supplemented by : "PSR-0010-ed2.0-EN 2023 12 08"           |
| Verifier accreditation number :     VH12                                                                                                                                                                                                               | Information and reference documents : <a href="http://www.pep-ecopassport.org">www.pep-ecopassport.org</a> |
| Date of issue:                     05-2025                                                                                                                                                                                                             | Validity period : 5 years                                                                                  |
| Independant verification of the declaration and data, in compliance with ISO 14025 : 2006                                                                                                                                                              |                                                                                                            |
| Internal : <input checked="" type="checkbox"/>                                                                                                                                                                                                         | External : <input type="checkbox"/>                                                                        |
| The PCR review was conducted by a panel of experts chaired by Julie Orgelet (DDemain)<br>PEPs are compliant with XP C08-100-1 : 2016 or EN 50693:2019<br>The components of the present PEP may not be compared with components from any other program. |                                                                                                            |
| Document complies with ISO 14025:2006 "Environmental labels and declarations. Type III environmental declarations"                                                                                                                                     |                                                                                                            |



*This document is intended to be only informative and non-contractual and does not create any right or obligation or commitment for Socomec towards its associates, customers or any other person or entity. All the values indicated in this document may change depending on many factors (use conditions, applications, installations, environment...). The life time mentioned in this document is only indicative and is not intended to be the minimal, maximal or average life time of the product.*

## Other covered references

For the products covered by the PEP other than the reference product, the environmental impacts of each phase of the lifecycle are calculated by multiplying the declared unit impacts values with the following extrapolation factors:

| Model           | M (A1-A3) | D (A4) | I (A5) | U (B1-B7) | EOL (C1-C4) |
|-----------------|-----------|--------|--------|-----------|-------------|
| 3DMA600P6-00000 | 1,00      | 1,00   | 1,00   | 1,00      | 1,00        |
| 3DMA600S6-00000 | 1,00      | 1,00   | 1,00   | 1,00      | 1,00        |
| 3DMA300P3-00000 | 0,71      | 0,71   | 1,00   | 0,50      | 0,69        |
| 3DMA300S3-00000 | 0,71      | 0,71   | 1,00   | 0,50      | 0,69        |
| 3DMA400P4-00000 | 0,76      | 0,76   | 1,00   | 0,65      | 0,75        |
| 3DMA400S4-00000 | 0,76      | 0,76   | 1,00   | 0,65      | 0,75        |
| 3DMA500P5-00000 | 0,88      | 0,88   | 1,00   | 0,83      | 0,87        |
| 3DMA500S5-00000 | 0,88      | 0,88   | 1,00   | 0,83      | 0,87        |
| 3DMA600P6-00000 | 1,19      | 1,19   | 1,25   | 1,00      | 1,19        |
| 3DMA600S6-00000 | 1,19      | 1,19   | 1,25   | 1,00      | 1,19        |
| 3DMA800S8-00000 | 1,13      | 1,13   | 1,00   | 1,31      | 1,14        |
| 3DMD800P8-00000 | 1,62      | 1,62   | 1,00   | 1,31      | 1,65        |
| 3DMD800S8-00000 | 1,62      | 1,62   | 1,00   | 1,31      | 1,65        |