



Certificate of Compliance

Certificate: 1902901 (LR112964)

Master Contract: 189705

Project: 2687234

Date Issued: January 20, 2014

Issued to: Socomec S.A.
rue de Westhouse 1
BP 10
Benfeld Cedex, 67235
France
Attention: Nadine Metz

The products listed below are eligible to bear the CSA Mark shown



Anne Drouin

Issued by: Anne Drouin

PRODUCTS

CLASS 4651 02 - SWITCHES - Dead-front (Open Type)

Fused load break switches and non-fused load break switches, open type, for use in industrial control equipment, 600V ac and less, 250V dc certified as disconnecting switches unless noted otherwise.

Part A: Fusible switches, Series FUSERBLOC followed by J30 A, J60A, J100A, J200A, J400A, rated 200kA at 600V ac and 100kA at 250V dc.

Reference	Cat. No. 3 poles	4 poles
FUSERBLOC J 30A	38603004	38606004
FUSERBLOC J 30A without test position	38503004	38506004
FUSERBLOC J 60A	38503006	38506006
FUSERBLOC J 60A without test position	38603006	38606006
FUSERBLOC J 100A	38603010	38606010
FUSERBLOC J 100A without test position	38503010	38506010
FUSERBLOC J 200A	38603020	38606020



Certificate: 1902901 (LR112964)

Master Contract: 189705

Project: 2687234

Date Issued: January 20, 2014

FUSERBLOC J 200A without test position	38503020	38506020
FUSERBLOC J 400A	38603040	38606040
FUSERBLOC J 400A without test position	38503040	38506040
FUSERBLOC J 400A with test position and equipped with mounting brackets	38603940	/

Fusible switches, Series FUSERBLOC followed by CC 30 A, J 30A, rated 100kA at 600V ac and 100kA at 250V dc.

Reference	Cat. No.	3 poles	4 poles
FUSERBLOC CC 30A	38603003		38606003
FUSERBLOC CC 30A without test position	38503003		38506003
FUSERBLOC J 30A	38603005		38606005
FUSERBLOC J 30A without test position	38503005		38506005

Part B Non-fusible switches, visible contact, Series SIRCO V followed by 60 A, 100 A, 200 A, 400A, rated 200kA at 600V ac and 100kA at 250V dc.

Reference	Cat. No.	3 poles	4 poles
SIRCO V 60A	27013006		27014006
SIRCO V 100A	27013010		27014010
SIRCO V 200A	27013020		27014020
SIRCO V 400A	27013039		27014039

APPLICABLE REQUIREMENTS

CAN/CSA-C22.2 No. 4-04 - Enclosed Switches