

Auswahlhilfe

Stromwandler

Typ	TRB 60	TRB 70	TRB 135	TCA 14	TCA 21	TCA 22	TCB 17-20	TCB 26-30	TCB 28-30	TCB 26-40	TCB 32-40	TCB 44-50
Format	Primärwicklung			Kabel			Kabel – Sammelschiene					
Klasse	0,5	0,5	0,5	1	0,5/1	1	1	0,5/1	0,5/1	1	0,5/1	0,5/1
Version 0,2 S			(1)			(2)		T2CB 26-30			T2CB 32-40	
	S. 2			S. 2			S. 2					

Bemessung (A)

0,5												
5	5											
10	...											
15	10											
20		5										
25		...										
30		40										
40												
50			40	*								
60			...	25								
75			80	...	40							
80				150	...							
100					150							
125			125			60						
150			...			...						
160			150			300						
200							100					
250							...					
300							600					
400												
500												
600												
750												
800												
1000												
1200												
1250												
1500												
1600												
2000												
2500												
3000												
4000												
5000												

Abmessungen

Höhe	75,5	85,5	85	65	65	65	65	61	70	75,5	88,5	98,5
Breite	61	71	135	45	45	49,5	49,5	75,5	49,9	61	71	86
Tiefe	35	45	60	30	30	35	50	48	68	48	58	58
Kabel (Ø mm)				14	21	22,5	17,5	26	28	26	32	44
Sammelschiene 1							20 × 5	30 × 10	30 × 10	32 × 18	40 × 10	50 × 12
Sammelschiene 2								20 × 10 (x2)		40 × 12	30 × 5 (x2)	40 × 10 (x2)
Sammelschiene 3												

* Klasse 1.

(1) Ausführung 0,2 S mit Primärwicklung: T2RB 115. Die Abmessungen unterscheiden sich von TRB 135.

(2) Closed-Loop-Ausführung 0,2 S mit Kabel: T2CA 225. Die Abmessungen unterscheiden sich von TCA 22.

Bar Index	Value	Range
1	200	800
2	300	1500
3	400	2000
4	750	1600
5	1000	3000
6	200	1600
7	300	2000
8	600	4000
9	1200	3000
10	400	2000
11	800	4000
12	100	400
13	250	800
14	250	1500
15	1000	5000


Gesamtkatalog 2025 2